Theoretical and Applied Fracture Mechanics 3 (1985) 263
North-Holland

AUTHOR INDEX *

Volume 3 (1985)

Baram, J., Material selection for a 2000 HP pump shaft, (1) 1–11
Branco, C.M., J.A. Martins Ferreira and J.C. Radon, Fatigue of fillet welded joints, (1) 13–22

Chang, C.I., see C.A. Griffis, (1) 41–48
Chang, C.I., see G.C. Sih, (1) 49–55
Chen, C., see G.C. Sih, (2) 125–139
Chen, E.P., Finite element analysis of a bimaterial interface crack, (3) 257–262
Cherevko, M.A., see A.N. Guz, (2) 151–155
Chow, C.L. and J. Xu, Application of the strain energy density criterion to ductile fracture, (3) 185–191

Drakos, G., see E.E. Gdoutos, (3) 227–232

Fischer, K.-F., Critique on fracture criteria in mixed-mode loading, (2) 85–95
Forman, R.G., A fracture mechanics study of the turbine wheel in the Space Shuttle auxiliary power unit, (2) 71–84

Gdoutos, E.E. and N. Hatzitrifon, Growth of an arc-crack in bonded dissimilar materials, (1) 57–62
Gdoutos, E.E., Stable growth of a crack interacting with a circular inclusion, (2) 141–150
Gdoutos, E.E. and G. Drakos, Crack initiation and growth in contact problems, (3) 227–232
Griffis, C.A., C.I. Chang and F.R. Stonesifer, Thermo-mechanical response of tension panels under intense rapid heating, (1) 41–48
Günther, W., Asymptotic elastic solution for two straight cracks of arbitrary length and location, (3) 247–255
Guz, A.N. and M.A. Cherevko, Fracture mechanics of unidirectional fibrous composites with metal matrix under compression, (2) 151–155
Guz, A.N. and V.M. Nazarenko, Symmetric failure of the halfspace with penny-shaped cracks in compression, (3) 233–245

Hatzitrifon, N., see E.E. Gdoutos, (1) 57–62
Heller, M., see J.Y. Mann, (2) 113–124

Jones, R., see J.Y. Mann, (2) 113–124

Madenci, E., see G.C. Sih, (1) 23–29
Madenci, E., see G.C. Sih, (1) 31–40
Mann, J.Y., R.A. Pell, R. Jones and M. Heller, Reducing the effects of rivet holes on fatigue life by adhesive bonding, (2) 113–124
Martins Ferreira, J.A., see C.M. Branco, (1) 13–22
Matic, P. and G.C. Sih, A pseudo-elastic material damage model, Part I: Strain energy density criterion, (3) 193–207
Matic, P. and G.C. Sih, A pseudo-elastic material damage model, Part II: Application to the scaling of specimen size, (3) 209–225

Nazarenko, V.M., see A.N. Guz, (3) 233–245
Nicoletto, G., Stress-intensity distributions for corner cracks emanating from open holes in plates of finite width, (1) 63–70

Ozen, M., see G.C. Sih, (1) 49–55

Pell, R.A., see J.Y. Mann, (2) 113–124

Radon, J.C., see C.M. Branco, (1) 13–22
Russo, R., Some classical theorems in fracture theory, (3) 179–184

Sih, G.C. and E. Madenci, Prediction of failure in weldments—Part I: Smooth joint, (1) 23–29
Sih, G.C. and E. Madenci, Prediction of failure in weldments—Part II: Joint with initial notch and crack, (1) 31–40
Sih, G.C., M. Ozen and C.I. Chang, Thermoplastic damage of a stretched plate caused by a moving energy source, (1) 49–55
Sih, G.C. and D.Y. Tzou, Rail-end bolt hole fatigue crack in three dimensions, (2) 97–111
Sih, G.C. and C. Chen, Non-self-similar crack growth in elastic-plastic finite thickness plate, (2) 125–139
Sih, G.C., see P. Matic, (3) 193–207
Sih, G.C., see P. Matic, (3) 209–225
Stonesifer, F.R., see C.A. Griffis, (1) 41–48

Tschegg, E.K., Fatigue crack growth in high and low strength steel under torsional loading, (2) 157–178
Tzou, D.Y., see G.C. Sih, (2) 97–111

Xu, J., see C.L. Chow, (3) 185–191

* The issue number is given in front of the page numbers.

0167-8442/85/$3.30 © 1985, Elsevier Science Publishers B.V. (North-Holland)